

DOUBLE 2X6 WITH 2X4 ON EACH SIDE-FLOOR TO CEILING AT EACH FLOOR

ANCHOR LOCATIONS


DETAIL G SCALE 1 : 4

- Battery Powered: 24 VDC Control System
- Rated Load: 500 lbs
- Speed: 15 fpm
- Max. Travel: 21'-0"
- Winding Drum Drive with dual 1/4" aircraft cables
- Automatic up/down controls
- Key Lock on controls
- Emergency Stop Switch and Alarm
- Recessed LED Car Light
- Status LED
- Door Position switch on Sliding Car Door
- Slack Cable Safety Device
- Final Limit Switch

SECTION A-A SCALE 1 : 16

SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAYING HOME CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAYING HOME CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	 <p>Staying Home Corporation          2501 Anaconda Rd          Harrisonville, MO 64701          816-380-2427          www.stayinghome.com</p>
DIMENSIONS ARE IN INCHES		DRAWN	7/16/2019	
TOLERANCES:		CHECKED		
FRACTIONAL: ±1/16		ENG APPR.		
ANGULAR: ±0.5°		MFG APPR.		TITLE:
ONE PLACE DECIMAL ±0.1		Q.A.		EZ6 - 90° FRONT/LEFT SIDE ENTRY
TWO PLACE DECIMAL ±0.01		PROJECT:		SIZE DWG. NO.
THREE PLACE DECIMAL ±0.005				B TYP - EZ6-90L
INTERPRET GEOMETRIC TOLERANCING PER:				SCALE: 1:96 WEIGHT:
MATERIAL				SHEET 1 OF 1
FINISH				
DO NOT SCALE DRAWING				